


<p>EK 溫度,風扇訊號接頭 (6Pin)</p> <ol style="list-style-type: none"> KTY84~130 + (馬達溫度) KTY84~130 - (馬達溫度) PTC130 + (馬達溫度) PTC130 - (馬達溫度) 散熱風扇 + DC24V(0.43A) 散熱風扇 - DC24V(0.43A) <p>附件 主軸開口鉸手 ER32 螺帽開口鉸手</p>	<p>刀具規格 筒夾ER 32 夾持刀具尺寸$\phi 2.0 \sim \phi 20$ 螺帽ER 32 (M40*P1.5)</p> <p>AS 前端氣幕入口 1~1.5 bar M5*P0.8 $\phi 4$管徑</p> <p>EP 馬達電纜線出線 (U.V.W.G) M25*P1.5-3/4"浪管</p> <p>EK 溫度,風扇,訊號接頭 6 pin</p>
---	--

馬達極數 4 極		S1/100%				S1/100%			
連續功率	Y								
馬達規格	Δ								
電壓 [V]	380	380	380	380	220	220	220	220	220
電流 [A]	9.7	7.9	7.5	7.3	5.9	16.8	13.8	13	12.7
頻率 [Hz]	250	400	534	667	800	250	400	534	667
轉速 [rpm]	7,500	12,000	16,000	20,000	24,000	7,500	12,000	16,000	20,000
功率 [kw]	3.8	3.8	3.8	3.8	3.0	3.8	3.8	3.8	3.0
轉矩 [Nm]	4.9	3.1	2.3	1.8	1.2	4.9	3.1	2.3	1.8

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference		
Designed by	Checked by	Approved by - date	Filename	Date	Scale



Name	WSR120g-A(3.8kw)		
Number	W95.09A.024.WSR	Edition	Sheet