



<p>EK 溫度,風扇訊號接頭 (6Pin)</p> <p>1 KTY84~130 + (馬達溫度)</p> <p>2 KTY84~130 - (馬達溫度)</p> <p>3 PTC130 + (馬達溫度)</p> <p>4 PTC130 - (馬達溫度)</p> <p>5 散熱風扇 + DC24V<0.43A></p> <p>6 散熱風扇 - DC24V<0.43A></p> <p>附件 主軸開口鉸手 ER32 螺帽開口鉸手</p>	<p>刀具規格</p> <p>筒夾ER 32 夾持刀具尺寸ϕ2.0~ϕ20</p> <p>螺帽ER 32 (M40*P1.5)</p>
	<p>AS 前端氣幕入口 1~1.5 bar M5*P0.8 ϕ4管徑</p>
	<p>EP 馬達電纜線出線 (U.V.W.G) M25*P1.5-3/4"浪管</p>
	<p>EK 溫度,風扇,訊號接頭 6 pin</p>

馬達極數 4 極		S1/100% Y				S1/100% Δ			
連續功率									
馬達編碼規格									
電壓 [V]	380	380	380	380	380	220	220	220	220
電流 [A]	13.1	11	10.5	8.9	8	24	20	19	14.6
頻率 [Hz]	240	400	534	667	800	240	400	534	667
轉速 [rpm]	7,200	12,000	16,000	20,000	24,000	7,200	12,000	16,000	20,000
功率 [kw]	5.5	5.5	5.5	4.7	4.2	5.5	5.5	5.5	4.7
轉距 [Nm]	7.3	4.4	3.3	2.2	1.7	7.3	4.4	3.3	2.2
Itemref	Quantity	Title/Name, designation, material, dimension etc				Article No./Reference			
Designed by	Checked by	Approved by - date		Filename	Date	Scale			
		Name	WSR120g-B(5.5kw)						
		Number	W95.09B.024.WSR	Edition	Sheet				