



<p>[EK] 溫度, 風扇訊號接頭 (6Pin)</p> <p>1 KTY84~130 + (馬達溫度)</p> <p>2 KTY84~130 - (馬達溫度)</p> <p>3 PTC130 + (馬達溫度)</p> <p>4 PTC130 - (馬達溫度)</p> <p>5 散熱風扇 + DC24V(0.43A)</p> <p>6 散熱風扇 - DC24V(0.43A)</p> <p>附件 主軸開口鉸手 ER32 螺帽開口鉸手</p>	<p>刀具規格</p> <p>筒夾ER 32 夾持刀具尺寸$\phi 2.0 \sim \phi 20$</p> <p>螺帽ER 32 (M40*M1.5)</p>		<p>[AS] 前端氣幕入口 1~1.5 bar M5*P0.8 $\phi 4$ 管徑</p> <p>[EP] 馬達電纜線出線 (U.V.W.G) M25*M1.5-3/4" 浪管</p> <p>[EK] 溫度, 風扇, 訊號接頭 6 pin</p>
	<p>[AS] 前端氣幕入口 1~1.5 bar M5*P0.8 $\phi 4$ 管徑</p>		
	<p>[EP] 馬達電纜線出線 (U.V.W.G) M25*M1.5-3/4" 浪管</p>		
	<p>[EK] 溫度, 風扇, 訊號接頭 6 pin</p>		

馬達極數 4 極										
連續功率	S1/100%					S1/100%				
馬達繞線規格	Y					Δ				
電壓 [V]	380	380	380	380	380	220	220	220	220	220
電流 [A]	24	20.2	19.4	17.2	6	42	35.1	33.7	30.8	10.5
頻率 [Hz]	234	400	534	667	800	234	400	534	667	800
轉速 [rpm]	7,000	12,000	16,000	20,000	24,000	7,000	12,000	16,000	20,000	24,000
功率 [kw]	10	10	10	9	2.1	10	10	10	10	2.1
轉距 [Nm]	13.9	8.1	6	4.3	0.8	13.9	8.1	6	4.3	0.8
Itemref	Quantity	Title/Name, designation, material, dimension etc					Article No./Reference			
Designed by	Checked by	Approved by - date			Filename	Date	Scale			
		Name	WSR120g-D(10kw)							
		Number	W95.09D.024.WSR	Edition	Sheet					